Huawei B715 is a new 4G <u>LTE Category 9</u> WiFi router which could support up to 64 wireless devices simultaneously. It could achieve peak download speed up to 450Mbps and upload speed to 50mbps. It has a built-in Ethernet port, you can connect an external hard drive or printer via the USB port and two external antennas. Here now, there is the Huawei B715s-23c available for network providers "Play" in Poland and "LMT" in Latvia.

Huawei B715s-23c LTE CPE Technical Specifications:

- * LTE Category 9 router
- * Support 4G LTE Band 1/3/7/8/20/28/32/38 (FDD 700/800/900/1500/1800/2100/2600MHz & TDD 2600MHz)
- * Support 3G DC-HSPA+/HSPA+/HSPA/UMTS: 2100MHz/900MHz
- * Support 2G EDGE/GPRS/GSM: 1900MHz/1800MHz/850MHz/900MHz
- * LTE DL 450Mbps/UL 50Mbps
- * 4 x LAN ports(One for LAN/WAN), 1 x telephone port
- * Two connectors for external antenna
- * SIM type: Micro SIM
- * Carrier Aggregation:
- -- (4G)2CA: CA_1A-3A, CA_1A-7A, CA_1A-8A, CA_1A-20A, CA_1A-28A, CA_1A-38A, CA_1C, CA_3A-7A, CA_3A-8A, CA_3A-20A, CA_3A-28A, CA_3A-32A, CA_3A-38A, CA_3C, CA_7A-7A, CA_7A-8A, CA_7A-20A, CA_7A-28A, CA_7A-32A, CA_7C, CA_20A-32A, CA_20A-38A, CA_38C
 -- (4G)3CA: CA_1A-3A-7A, CA_1A-3A-8A, CA_1A-3A-20A, CA_1A-3C, CA_1A-7A-20A, CA_1A-7C, CA_3A-7A-8A, CA_3A-7A-20A, CA_3A-7A-28A, CA_3A-7A-28A, CA_3A-7A-28A, CA_3A-20A-32A, CA_3C-7A, CA_3C-20A, CA_7A-20A-38A

Huawei B715s-23c LTE Router mainly supports the following features:

- * Access to LTE wireless networks
- * Access to Gigabit Ethernet networks
- * High-speed data access
- LTE FDD: 4*4MIMO+2CA 582Mbps
- LTE TDD: 4*4MIMO+2CA 426Mbps
- DC-HSPA+: DL 42 Mbit/s, UL 5.76 Mbit/s
- HSPA+: DL 21 Mbit/s (64QAM) / 28 Mbit/s (MIMO), UL 5.76 Mbit/s
- HSPA: DL 14.4 Mbit/s, UL 5.76 Mbit/s
- WCDMA PS: 384 kbit/s
- EDGE: DL 296 kbit/s, UL 236.8 kbit/s
- GPRS: 85.6 kbit/s
- * Complies with wireless 802.11b/g/n/ac standards with dual-band(2.4GHz and 5GHz)
- * Support up to 64 wireless devices
- * SMS
- * IPv4 /IPv6 dual stack
- * Compatibility with RJ11 telephone ports; support VoLTE voice(customizable function), can be set to Voice over Internet Protocol (VoIP) voice mode or Circuit Switch (CS) voice mode
- * External LTE antenna port
- * Support for Huawei HiLink App
- * WPS 2.0
- * HOTA updates

- * Built-in DHCP Server, DNS RELAY and NAT
- * Security services. Provides instant protection to block potential security risks and intrusion attempts
- * Windows 7, Windows 8, Windows 8.1, Windows 10 (does not support Windows RT), MAC OS X 10.9, 10.10, 10.11 and 10.12 with latest upgrades
- * User-friendly design of LED indicator. Easy to observe the status of equipment
- * External port
- One power adapter port
- Three LAN port (RJ45)
- One LAN/WAN port (RJ45)
- One phone port (RJ11)
- Two external LTE antenna ports(SMA-female Type)
- One micro-SIM card slot
- * Power consumption: < 12W
- * AC/DC power supply
- AC: 100 V 240 V DC: 12 V/1 A
- * Temperature
- Working temperature: 0°C to 40°C
- Storage temperature: -20°C to +70°C
- * Humidity: 5% 95%(Non-condensing)
- * Dimensions(Maximum): 240mm × 448mm × 47mm
- * Weight: About 448g (excluding the power adapter)